

PRODUCT NAME: **JSR NFC FZX F112**

MATERIAL SAFETY DATA SHEET

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product Identifier: **JSR NFC FZX F112**
General Use: Overcoat material for Photoresist application
Product Description: (Meth)acrylic Resin Solution

MANUFACTURER:
JSR Corporation
1-9-2, Higashi-Shinbashi,
Minato-ku, Tokyo
105-8640 Japan

EMERGENCY TELEPHONE NUMBERS:
CHEMTREC: +1-800-424-9300
(in USA) 24Hrs Every day
Telephone: +81-3-6218-3592
9:15-17:45 Jpn M-F
Facsimile: +81-3-6218-3692
24Hrs Every day

DISTRIBUTOR:
JSR Micro Inc.
1280 North Mathilda Ave.,
Sunnyvale, CA 94089
Telephone: +1-408-543-8800

2. COMPOSITION / INFORMATION ON INGREDIENTS

Component	%	CAS No.
(Meth)acrylic resin	1-10	Proprietary
Melamine resin	Less than 1	Proprietary
Additive	Less than 3	Proprietary
Water	1-5	7732-18-5
Methyl isobutyl carbinol (MIBC)	85-95	108-11-2

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

Light brown liquid with an alcohol-like odor.

POTENTIAL HEALTH EFFECTS

INHALATION:

May cause irritation to nose and throat.

EYE CONTACT:

Eye contact may cause mild irritation.

SKIN CONTACT:

Prolonged and repeated contact with skin may cause irritation and dermatitis.

INGESTION:

Swallowing may cause nausea and pain in esophagus and stomach.

CARCINOGENICITY:

Not known to be carcinogenic.

NTP: No

IARC MONOGRAPHS: No

OSHA Regulated: No

SIGNS AND SYMPTOMS:

Eye and skin irritation, nausea, pain in esophagus, stomach, and anesthesia.

NFPA RATINGS (SCALE 0 – 4): HEALTH=2; FIRE=2; REACTIVITY=0

PRODUCT NAME: **JSR NFC FZX F112**

4. FIRST AID MEASURES

INHALATION:

Remove exposed person to fresh air; perform artificial respiration if necessary.

EYE CONTACT:

Immediately flush eyes with plenty of water at least 15 min. Call a physician.

SKIN CONTACT:

Flush skin with water and soap.

INGESTION:

Give large quantities of water, contact a poison center and call physician immediately.

NOTE TO PHYSICIAN:

Treatment may vary with condition of victim and specifics of incident.

5. FIRE-FIGHTING MEASURES

GENERAL HAZARD:

Combustible liquid. May release vapors that form flammable mixtures when temperatures are at or above the flash point. Toxic gases will form upon combustion.

EXTINGUISHING MEDIA:

Carbon dioxide, alcohol foam or dry chemical.

SPECIAL FIRE FIGHTING PROCEDURES:

Water should be used to keep fire exposed containers cool and to disperse vapors. Firefighters should wear self-contained breathing apparatus.

FIRE AND EXPLOSION HAZARDS:

Combustible liquid. Toxic gases, smoke, and oxides of Carbon will form upon combustion.

6. ACCIDENTAL RELEASE MEASURES

LARGE SPILL/SMALL SPILL:

For indoor spills, provide increased ventilation as required to minimize exposure. Contain, absorb, and cleanup the spill as indicated in the appropriate land or water section below. Dispose of absorbent and other waste in an appropriate chemical waste container. Wear proper personal protective equipment. Wash thoroughly after handling.

LAND SPILL:

Dike or absorb with inert absorbent material and transfer to D.O.T. container for disposal.

WATER SPILL:

Remove from surface by skimming or with suitable absorbent.

7. HANDLING AND STORAGE

GENERAL:

Store in original container in a dry area. Avoid heat, sunlight, and ignition sources. Open only under safe light and well ventilated conditions. Loosen closure cautiously before opening. When using this substance: (a) avoid breathing the substance; (b) avoid ingestion; (c) use respiratory protection when in dust or mist form. Wear chemical goggles, resistant gloves and protective clothing to prevent contact. Wash thoroughly after handling.

STORAGE TEMPERATURE: 32 to 50°F (0 to 10°C)

STORAGE PRESSURE: Atmospheric

PRODUCT NAME: **JSR NFC FZX F112**

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS:

The use of local exhaust ventilation is recommended to control emissions near the source. Laboratory samples should be handled in a fumehood. Provide mechanical ventilation of confined spaces. Use explosion-proof ventilation equipment.

PERSONAL PROTECTION

RESPIRATORY PROTECTION:

Under conditions of frequent use or heavy exposure, respiratory protection may be needed. Respiratory protection is ranked in order from minimum to maximum. Consider warning properties before use. NIOSH approved respirators as follows:
 Any chemical cartridge respirator with organic vapor cartridge(s).
 Any chemical cartridge respirator with a full facepiece and organic vapor cartridge(s).
 Any air-purifying respirator with a full facepiece and an organic vapor canister.
 For Unknown Concentrations or Immediately Dangerous to Life or Health.
 Any supplied-air respirator with full facepiece and operated in a pressure-demand or other positive-pressure mode in combination with a separate escape supply.
 Any self-contained breathing apparatus with a full facepiece.

SKIN PROTECTION:

Wear impermeable gloves and clothing during activities where there is potential for direct skin contact with chemical.

EYE PROTECTION:

Wear primary eye protection such as splash resistant safety goggles with a secondary protection faceshield. Provide an emergency eye wash station and quick drench shower in the immediate work area.

EXPOSURE GUIDELINE (S):

OSHA HAZARDS (29 CFR 1910.1200) Exposure Limits 8 hrs. TWA (ppm)

COMPONENT	OSHA PEL	ACGIH TLV
(Meth)acrylic resin	Not established	Not established
Melamine resin	Not established	Not established
Additive	Not established	Not established
MIBC	25	25

9. PHYSICAL AND CHEMICAL PROPERTIES

Vapor Pressure: 4.8 hPa at 20°C
 Specific Gravity: 0.8 - 0.9
 Solubility in water: Poor
 Boiling Point: 132°C
 Flashpoint and Method: 43°C(estimated)
 Flammable Limits: LFL; 1.0% UFL; 5.5 %
 Autoignition Temperature: 327°C

PRODUCT NAME: **JSR NFC FZX F112**

10. STABILITY AND REACTIVITY

INCOMPATIBILITY: (SPECIFIC MATERIALS TO AVOID)

Strong oxidizing agents, strong acids, strong bases.

STABILITY: (CONDITIONS TO AVOID)

Materials containing similar structural groups are normally stable. This material maybe sensitive to peroxide formation.

HAZARDOUS DECOMPOSITION PRODUCTS:

Combustion will produce toxic vapors and gases.

HAZARDOUS POLYMERIZATION:

May not occur.

11. TOXICOLOGICAL INFORMATION

SOLVENT (MIBC):

ACUTE TOXICITY

Oral	LD50	rat	2,590 mg/kg
Dermal	LD50	rabbit	3,560 uL/kg

Melamine resin:

ACUTE TOXICITY

Oral	LD50	rat	12,300 uL/kg
Dermal	LD50	rabbit	10 mL/kg

(Meth)acrylic resin: No information available

Additive: No information available

12. ECOLOGICAL INFORMATION

SOLVENT (MIBC):

FISH TOXICITY: 360,000 ug/L 24 day(s) LC50 (Mortality)

Goldfish (*Carassius auratus*)

OTHER TOXICITY: 656,000 ug/L 48 hour(s) LC50 (Mortality)

Clawed toad (*Xenopus laevis*)

Melamine resin: No information available

(Meth)acrylic resin: No information available

Additive: No information available

13. DISPOSAL CONSIDERATION

The user of this product must properly characterize the waste generated from the use of this product in accordance with all applicable federal, state and/or local laws and regulations in order to determine the proper disposal of the waste in accordance with all applicable federal, state and/or local laws and regulations.

14. TRANSPORT INFORMATION

TRANSPORTATION AND HAZARDOUS MATERIALS DESCRIPTION:

Package and transport in accordance with Department of Transportation (DOT) and other regulatory agency requirements.

U. S. DOT PROPER SHIPPING NAME: Resin solution, Class 3, UN1866, III

IATA PROPER SHIPPING NAME: Resin solution

IDENTIFICATION NUMBER: UN 1866

PRODUCT NAME: **JSR NFC FZX F112**

15. REGULATORY INFORMATION

US

OSHA HAZARD COMMUNICATION STANDARD, 29 CFR 1910.1200: Ensure that the hazards associated with this product are transmitted to employees by means of a hazard communications program, in accordance with federal and state Occupational Safety and Health Administration (OSHA) regulations.

CERCLA/SUPERFUND HAZARD CATEGORY: At the time of this document's preparation, one of the ingredients of this product was listed in 40 CFR 302.4. (Less than 0.1% of BUTYL ALCOHOL: 5000 LBS RQ) The list should be periodically checked for applicable updates.

SARA 313 INFORMATION: At the time of this document's preparation, one of the ingredients of this product was listed in 40 CFR 372. (Less than 0.1% of BUTYL ALCOHOL) The list should be periodically checked for applicable updates.

TOXIC SUBSTANCES CONTROL ACT (TSCA): All of the compounds in this product are on the TSCA Inventory and/or are subject to a Low Volume Exemption. In accordance with federal regulations, this material shall be used only to industrially manufacture integrated circuits. In particular, this material shall not be distributed to any person, other than for disposal, until after it has been completely reacted. All users must utilize the worker protection measures and environmental release controls specified in this Material Safety Data Sheet and in EPA and OSHA regulations. Acknowledgment of receipt of this Material Safety Data Sheet shall be considered acknowledgment that the user will comply with these requirements.

CALIFORNIA PROPOSITION 65 WARNING: At the time of this document's preparation, one or more constituents of this product were included on the California Proposition 65 list of chemicals known to cause cancer and birth defects or other reproductive harm. The list should be periodically checked for applicable updates.

16. OTHER INFORMATION

REVISION SUMMARY

March 3, 2008	Original MSDS established.
March 26, 2008	Revision 1 established.
July 21, 2009	Revision 2 established.
April 14, 2010	Revision 3 established.

To the best of our knowledge, the information contained herein is accurate. However, neither JSR Corporation nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards, which exist.