

MATERIAL SAFETY DATA SHEET



SECTION 1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

MANUFACTURER/SUPPLIER NAME: Clariant Corporation, AZ Electronic Materials

PO Box 3700, 70 Meister Avenue

Somerville, NJ 08876-1258

TELEPHONE NUMBERS: Emergency-CHEMTREC: (800) 424-9300

> Product Safety Information: (908) 429-3593 (800) 515-4164

Customer Service:

PRODUCT NAME:

AZ(R) EBR SOLVENT

None

MSDS NO.

SYNONYMS:

7091

REVISION DATE:

10/15/1999

DATE PRINTED:

07/19/2000

SECTION 2. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name & CAS Number	Weight Percent	Hazardous?	NJ Trade Secret#	Ingredient Synonyms	Other Information:
1-Methoxy-2-propanol acetate 000108-65-6	100	Yes	N/A	Propylene glycol monomethyl ether acetate, PGMEA, PMA	None

SECTION 3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW:

Clear, colorless liquid with a strong characteristic odor. Partially dissolves in water. OSHA combustible liquid; DOT flammable liquid. Irritating on contact or inhalation.

POTENTIAL HEALTH EFFECTS:

Eve:

Causes eye irritation.

Skin:

Causes skin irritation.

Ingestion:

May be harmful if swallowed.

Inhalation:

Single exposure unlikely to be hazardous. High vapor concentration causes irritation to the nose, throat, and lungs.

lystemic Effects:

No hazard in normal industrial use.

Reproductive & birth defects:

Clariant Corporation, AZ Electronic Materials AZ(R) EBR SOLVENT 7091 REVISION DATE: 10/15/1999

Exposures having no adverse effect on the mother should have no effect on the fetus.

Relevant Routes of Exposure:

Inhalation. Skin absorption. Eve contact with liquid and vapors.

Medical Conditions Aggravated:

Preexisting skin, eye, and respiratory conditions may be aggravated.

ENVIRONMENTAL OVERVIEW:

Not all components tested, major component has little or no environmental hazard.

SECTION 4. FIRST AID MEASURES

FIRST AID PROCEDURES:

Inhalation:

Remove victim to fresh air. Consult physician if irritation occurs.

Eye Contact:

Flush thoroughly with water for 15 minutes. Get immediate medical help.

Skin Contact:

Immediately remove contaminated clothing and wash affected area thoroughly with soap and water. Consult physician if exposure is extensive or if irritation occurs.

Ingestion:

If person is conscious, give water or milk to dilute stomach contents. Never give anything by mouth to an unconscious person. Consult physician.

NOTE TO PHYSICIANS:

Administer oxygen if there is difficulty in breathing.

SECTION 5. FIRE FIGHTING MEASURES

Flash point:

116 deg F, Closed Cup

Extinguishing Media:

Carbon dioxide, water, alcohol foam, dry chemical.

Special Procedures:

Use self-contained breathing apparatus and full protective clothing. Use water spray to cool drums in fire area.

Unusual hazards:

Solvent vapors. Emits toxic fumes under fire conditions.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Spill or Leak Procedures:

Wearing appropriate personal protective equipment, contain spill, ventilate area of spill or leak, remove all sparking devices or ignition sources, collect onto inert absorbent, and place in a suitable container.

SECTION 7. HANDLING AND STORAGE

Handling:

Keep away from heat and flame. Wash thoroughly after handling. Keep container closed. Avoid breathing vapors and contact with skin, eyes, and clothing. Use only with adequate ventilation and proper protective eyewear, gloves, and clothing.

Clariant Corporation, AZ Electronic Materials AZ(R) EBR SOLVENT 7091 10/15/1999

REVISION DATE:

Storage:

Store at appropriate temperature. See label for details, Store in original container, Transport and store under dry conditions tightly closed. May liberate combustible solvent vapors.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Controls:

Use local exhaust ventilation.

Personal Protective Equipment (PPE):

Clothing suitable to prevent skin contact. Rubber gloves. Chemical cartridge respirator recommended for exposures exceeding TLV. Safety eyewear to protect against splashes.

Exposure Guidelines:

Chemical Name & CAS Number	Weight Percent	Manufacturer's TWA TLV*	ACGIH TWA TLV*	OSHA PEL ⁴	NIOSH REL*	AIHA WEEL*
1-Methoxy-2-propanol acetate 000108-65-6	100	100 ppm				100 ppm (541 mg/m ³¹

^{*}TWA TLV = Time Weighted Average Threshold Limit Value

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:

Clear, colorless liquid.

Odor:

Strong, characteristic odor.

Physical State:

Liquid

Vapor Pressure

3.7 torr

Boiling Point:

140 C

Solubility in water:

PGMEA 16%

Specific gravity:

0.965

VOC:

965 g/L

Evaporation rate

(butyl acetate=1):

0.33 (PGMEA)

% Volatile:

100%

SECTION 10. STABILITY AND REACTIVITY

Chemical Stability:

Stable.

Hazardous Polymerization:

Will not occur.

Conditions to Avoid:

Avoid contact with oxidizing agents. Avoid contact with strong acids. Avoid contact with alkaline materials.

Hazardous Decomposition Products:

Thermal decomposition may generate carbon dioxide and carbon monoxide.

ACGIH = American Conference of Governmental Industrial Hygienists

SHA PEL = Occupational Safety and Health Administration Permissable Exposure Limit

NIOSH REL = National Institute of Occupational Safety and Health Recommended Exposure Limit

AIHA WEEL = American Industrial Hygiene Association Workplace Environmental Exposure Level

[&]quot;Skin Notation

[&]quot;"Hoechst Celanese Workplace Exposure Level (HCC WEL); included is a "no contact" recommendation for NMP due to its skin absorption properties.

Clariant Corporation, AZ Electronic Materials AZ(R) EBR SOLVENT 7091 REVISION DATE: 10/15/1999

SECTION 11. TOXICOLOGICAL INFORMATION

Carcinogen:

IARC: NO NTP: NO OSHA: NO

Ingredient Toxicity Data:

Chemical Name & CAS Number	Weight Percent	oral rat LD50	skin rbt LD50	inh rat LC50	
1-Methoxy-2-propanol acetate 000108-65-6	100	8.5 g/kg/male, 10.0 g/kg/female	>5.0 g/kg	>4350 ppm	

TOXICITY HAZARD STATEMENTS FOR PRODUCT:

Eye Effects:

Testing in rabbits shows that the material is a mild eye irritant.

Skin Effects:

Testing in animals shows that this material is a nonirritant; however, the product is considered a human skin irritant. Based on animal testing, the acute toxicity of this material via the dermal route is classified as not harmful (rabbit or rat dermal '.D50 greater than 2000 mg/kg)

Acute Oral Effects:

Testing in animals shows that this material is not harmful (rat acute oral LD50 >5000 mg/kg).

Acute Inhalation:

Testing in animals shows that this material is not harmful (LC50 greater than 10,000 ppm or 200 mg/L) This material is considered irritating to the respiratory tract.

Subchronic Effects:

Long term, high level exposure to PGMEA has resulted in adverse effects to the livers and kidneys of experimental animals.

Chronic Effects:

No information available.

Mutagenicity/Genotoxicity:

Testing of this material suggests no genotoxic hazard.

SECTION 12. ECOLOGICAL INFORMATION

Ingredient Ecological Toxicity Data:

Chemical Name & CAS Number	Weight Percent	Fish LC50	Daphnia EC50	Algae IC50
1-Methoxy-2-propanol acetate 000108-85-8	100	161 mg/L	408 mg/L	

Clariant Corporation, AZ Electronic Materials AZ(R) EBR SOLVENT 7091 REVISION DATE: 10/15/1999

Environmental hazard information statements (using EU classification criteria):

Toxicity to fish:

Based on testing, this material is classified as: Not Harmful (LC50 > 100 mg/L).

Toxicity to daphnids:

Based on testing, this material is classified as: Not Harmful (EC50 greater than 100 mg/L).

Toxicity to Algae:

No data available.

Environmental Fate:

No information.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal:

Consult local, state, and federal regulations. For disposal, this material is a flammable hazardous waste under RCRA.

SECTION 14. TRANSPORT INFORMATION

DOT/IATA Shipper Entry:

Flammable liquid, n.o.s. (1-methoxy-2-propanol acetate), 3, UN 1993, III.

Other Information:

Not regulated for surface transportation in non-bulk containers under 119 gallons.

SECTION 15. REGULATORY INFORMATION

TSCA Inventory Status:

This product is listed on the TSCA Inventory.

SARA Title III section 313:

This product is not subject to SARA Title III Section 313 reporting requirements under 40CFR372.

OSHA Physical Hazards:

Combustible liquid.

OSHA Health Hazards:

Eye Hazard, Irritant, Nervous System Toxin, Skin Hazard, Lung Toxin,

SARA (311, 312) Hazard Class(es):

Acute health hazard. Fire hazard.

SECTION 16. OTHER INFORMATION

HMIS Ratings:

Health = 2; Flammability = 2; Reactivity = 0; PPE=G

NFPA Ratings:

Health = 2; Flammability = 2; Reactivity = 0; Special Hazard = None.

(R) and TM indicate trademarks of Clariant AG, its business partners or suppliers. The information herein is provided in good faith, but no warranty, express or implied, is made with respect to such information.